## Monitoring Data Record

Project Title: U-2524AB (Site 3) COE Action ID: 200321137
Stream Name: <u>UT #3 Reddicks Creek</u> DWQ Number: <u>030909</u>
City, County and other Location Information: <u>Greensboro Western Loop, Guilford Co.</u>
Sta. 34+00 to Sta. 37+10 -L-
Date Construction Completed: Water was turned into the stream on June 2005 and planted
January 2007. Monitoring Year: (2) of 5
Ecoregion: 8 digit HUC unit 03030002
USGS Quad Name and Coordinates:
Rosgen Classification:
Length of Project: 692' Urban or Rural: Urban Watershed Size:
Monitoring DATA collected by: M. Green & J. Young Date: 1/16/08
Applicant Information:
Name: NCDOT Roadside Environmental Unit
Address: 1425 Rock Quarry Road Raleigh, NC 27610
Telephone Number: (919) 861-3772 Email address: mlgreen@dot.state.nc.us
Consultant Information:
Name:
Address:
Telephone Number: Email address:
Project Status: Complete
Monitoring Level required by COE and DWQ (404 permit/ 401 Cert.): Level  Monitoring Level 1 requires completion of Section 1, Section 2 and Section 3
NIOHHOHIB LAAVA I KAHIKS COHDICHOH OL SECHOL L SECHOL Z UNG SECHOL X
Permit States: NCDOT shall perform the following components of Level I monitoring twice
<b>Permit States</b> : NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant
<b>Permit States</b> : NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during
<b>Permit States</b> : NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is
<b>Permit States</b> : NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that
<b>Permit States</b> : NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in
<b>Permit States</b> : NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that
<b>Permit States</b> : NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in
Permit States: NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in consultation with resource agencies, may determine that further monitoring is not required.  Section 1. PHOTO REFERENCE SITES
Permit States: NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in consultation with resource agencies, may determine that further monitoring is not required.  Section 1. PHOTO REFERENCE SITES
Permit States: NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in consultation with resource agencies, may determine that further monitoring is not required.  Section 1. PHOTO REFERENCE SITES (Monitoring at all levels must complete this section)
Permit States: NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in consultation with resource agencies, may determine that further monitoring is not required.  Section 1. PHOTO REFERENCE SITES (Monitoring at all levels must complete this section)  Total number of reference photo locations at this site: 6 reference points, 2 photos at each
Permit States: NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in consultation with resource agencies, may determine that further monitoring is not required.  Section 1. PHOTO REFERENCE SITES (Monitoring at all levels must complete this section)  Total number of reference photo locations at this site: 6 reference points, 2 photos at each
Permit States: NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in consultation with resource agencies, may determine that further monitoring is not required.  Section 1. PHOTO REFERENCE SITES (Monitoring at all levels must complete this section)  Total number of reference photo locations at this site: 6 reference points, 2 photos at each Dates reference photos have been taken at this site: 2/16/07, 7/19/07, 1/16/08  Individual from whom additional photos can be obtained (name, address, phone):
Permit States: NCDOT shall perform the following components of Level I monitoring twice each year for the 5 year monitoring period (summer and winter): Reference photos, plant survival, and visual inspection of channel stability. If less than two bankfull events occur during the first 5 years, NCDOT shall continue monitoring until the second bankfull event is documented. The bankfull events must occur during separate monitoring years. In the event that the required bankfull events do not occur during the 5 year monitoring period, the USACE, in consultation with resource agencies, may determine that further monitoring is not required.  Section 1. PHOTO REFERENCE SITES  (Monitoring at all levels must complete this section)  Total number of reference photo locations at this site: 6 reference points, 2 photos at each Dates reference photos have been taken at this site: 2/16/07, 7/19/07, 1/16/08

If required to complete Level 3 monitoring <u>only</u> stop here; otherwise, complete section 2.

Attacn	plan sheet indica	ing reference p	onotos.			
Identi	fy specific prob	em areas (mi	ssing, stresse	d, damaged or	dead plantii	ngs):
Estim	ated causes, and	proposed/rec	quired remedi	ial action:		
ADD	ITIONAL COM	IMENTS: V	egetation is dorr	mant at this time.	Streambank re	eforestation include
						and river birch. Th
	bank reforestation			· · · · ·		
			<u></u>			

Section 2. PLANT SURVIVAL

If required to complete Level 1 and Level 2 monitoring only stop here; otherwise, complete section 3.

## Section 3. CHANNEL STABILITY

**Visual Inspection:** The entire stream project as well as each in-stream structure and bank stabilization/revetment structure must be evaluated and problems addressed.

Report on the visual inspection of channel stability. <u>Physical measurements of channel stability/morphology will not be required.</u> Include a discussion of any deviations from as-built and an evaluation of the significance of these deviations and whether they are indicative of a stabilizing or destabilizing situation.

The UT #3 Reddicks Creek stream relocation is stable for the Year 2 winter evaluation. There was some minor ban
scouring noted on the left bank at Photo Point #6 (upstream). NCDOT will continue to monitor this stream
relocation.

1/16/08	PP#6	Station	Station	Station	Station
	Sta. 36+80	Number	Number	Number	Number
Structure					
Type					
Is water					
piping					
through or					
around					
structure?					
Head cut or					
down cut					
present?					
Bank or scour	Minor Bank				
erosion	Scouring				
present?					

## UT #3 Reddicks Creek

Site 3



Photo Point #1 (Upstream)



Photo Point #1 (Downstream)



Photo Point #2 (Upstream)



Photo Point #2 (Downstream)



Photo Point #3 (Upstream) Year 2 Winter – January 2008



Photo Point #3 (Downstream)

## UT #3 Reddicks Creek

Site 3



Photo Point #4 (Upstream)



Photo Point #4 (Downstream)



Photo Point #5 (Upstream)



Photo Point #5 (Downstream)



Photo Point #6 (Upstream) Year 2 Winter – January 2008



Photo Point #6 (Downstream)